### Strand Pendant Lamp

"The Strand Pendant Lamp is formed from a sprayed cocoon material with its cloud-like appearance that tightly clings to a spinning steel frame. It consists of tiny strands for a complex, intriguing structure that shrouds the light source while acting as its diffuser. With its see-through expression, the cocoon material allows for the Strand Pendant Lamp to filter light for a warm, comfortable glow."

### — Benjamin Hubert



**Designed by** Benjamin Hubert / 2019

EnvironmentIndoorCountry of ProductionItalyPreassembledYes.

**Description** The Strand Pendant Lamp is designed with soft, playful forms for a modern expression. The design

provides both diffused lighting and direct lighting, the latter through its top and bottom opening. The design is made in a sprayed cocoon material that consists of tiny strands for a complex, intriguing structure that, paired with its modern form, gives the Strand Pendant Lamp an almost cloud-like appearance. With its cocoon material filtering light through for a warm, comfortable glow, the Strand Pendant Lamp hovers lightly in space, bringing comfort, harmony and a refined

sensitivity to any room.

Material The Strand Pendant Lamp is made of a cocoon layer with an inner steel structure, a PVC cord and

PVC covered steel wire.

Clean with soft dry cloth only. Always switch off the electricity supply before cleaning.

 ${\bf Cord \ length} \hspace{1.5cm} 300, 500 \ {\bf cm} \ / \ 118.1", 196.9"$ 

 Light source included
 Closed - 17.7", Closed - 23.5", Closed - 31.5", Open - 11", Open - 16", Open - 23.5": No

 Ceiling Cap included
 Closed - 17.7", Closed - 23.5", Closed - 31.5", Open - 11", Open - 16", Open - 23.5": Yes

Dimmable function Yes.

Additional information Please note that the Open Ø60, Closed Ø45, Ø60 and Ø80 come with a wire suspension system with

three metal wires. Metal wires 490 cm. Cord length 500 cm. Total possible suspension length from

ceiling 480 cm.



## **Strand Pendant Lamp**

#### Dimensions

Closed - 23.5"

 Length:
 60 cm / 23.6"

 Height:
 54,8 cm / 21.6"

 Width:
 60 cm / 23.6"

 Diameter:
 60 cm / 23.6"

 Cord Length:
 500 cm / 196.9"



Closed - 31.5"

 Length:
 80 cm / 23.9"

 Height:
 60,8 cm / 23.9"

 Width:
 80 cm / 23.9"

 Diameter:
 80 cm / 31.5"

 Cord Length:
 500 cm / 196.9"



Closed - 17.7"

 Length:
 45 cm / 17.7"

 Height:
 36,4 cm / 14.3"

 Width:
 45 cm / 17.7"

 Diameter:
 45 cm / 17.7"

 Cord Length:
 500 cm / 196.9"



Open - 23.5"

 Length:
 60 cm / 23.6"

 Height:
 40,3 cm / 15.9"

 Width:
 60 cm / 23.6"

 Diameter:
 60 cm / 23.6"

 Cord Length:
 500 cm / 196.9"



Open - II"

 Length:
 28 cm / 11"

 Height:
 37,4 cm / 14.7"

 Width:
 28 cm / 11"

 Diameter:
 28 cm / 11"

 Cord Length:
 300 cm / 118.1"



Open - 16"

 Length:
 40 cm / 15.7"

 Height:
 50,2 cm / 19.8"

 Width:
 40 cm / 15.7"

 Diameter:
 40 cm / 15.7"

 Cord Length:
 300 cm / 118.1"



Ready-to-ship

White - Open White - Closed

#### Lamp rating

	Closed - 23.5"	Closed - 31.5"	Closed - 17.7"	Open - 23.5"
Voltage	120V	120V	120V	120V
Frequency	60Hz	60Hz	60Hz	60Hz
IP Rating	IP20	IP20	IP20	IP20
Socket	1 v E26 May 60W May	1 v E26 May 60W May	1 v E26 May 60W May	1 v E26 Mov

30W CLFMax. 25W LED 30W CLF Max. 25W LED 30W CLF Max. 25W LED 30W CLF Max. 25W LED

 Open-II"
 Open-I6"

 Voltage
 120V
 120V

 Frequency
 60Hz
 60Hz

 IP Rating
 IP20
 IP20

Socket 1 x E26 Max. 40W Max. 1 x E26 Max. 40W Max.

13W CLF Max. 13W LED 13W CLF Max. 13W LED

# **Strand Pendant Lamp**

#### Light source recommendation

Closed - 31.5" Closed - 23.5" Lamp Base E26 E26 Ø125 x 175 mm Ø125 x 175 mm Dimensions Light Source Shape G125 G125 Light Source Type LED LED Max. 60W Max. 30W CLF Max. 60W Max. 30W Max Voltage

LED

Max. 25W LED CLFMax. 25W LED

LED

Open - II" Open - 16" Lamp Base E26 E26 Dimensions Ø80 x 115 mm Ø80 x 115 mm Light Source Shape G80 G80

Max. 40WMax. 13W Max. 40WMax. 13W Max Voltage CLFMax. 13W LED CLFMax. 13W LED

Tests, Labels  $\boldsymbol{\delta}$  Certifications

Safety & Regulations

Light Source Type

cETLus or cULus









Closed - 17.7"

Ø125 x 175 mm

Max. 60WMax. 30W

CLFMax. 25W LED

E26

G125

LED

Open - 23.5"

Ø125 x 175 mm

Max. 60WMax. 30W

CLFMax. 25W LED

E26

G125

LED









**Explore Assets** 

**DOWNLOADSITE** 

